

## Medina

<b>Construction</b>	1/10" Loop
<b>Manufacturing</b>	Tufted
<b>Pile material</b>	100% Polyamid Solution Dyed
<b>Primary backing</b>	Synthetic
<b>Secondary backing</b>	Modified bitumen enhanced with a thermoplastic elastomer, reinforced with a glass fibre fleece covered with 100% PES fleece
<b>Total weight</b>	4585 g/m <sup>2</sup>
<b>Pile weight</b>	615 g/m <sup>2</sup>
<b>Pile above backing</b>	380 g/m <sup>2</sup>
<b>Total height</b>	6,8mm
<b>Pile height</b>	3,0mm
<b>Pile density</b>	0,127 g/cm <sup>3</sup>
<b>Tuft density</b>	147.750 m <sup>2</sup>
<b>Fire resistance</b>	C <sub>fls</sub> 1
<b>Fastness to light</b>	ISO 105-B02 ≥ 7
<b>Rubbing fastness</b>	EN ISO 105-X12 ≥ 4
<b>Colour fastness to water</b>	EN ISO 105-E01 ≥ 4
<b>Thermal resistance</b>	ISO 8302 0,055 qm K/W
<b>Impact noise rating</b>	ΔL <sub>w</sub> ISO 140-8 26 dB
<b>Sound absorption</b>	ISO354 Hz    125    250    500    1000    2000    4000 S    0,02    0,02    0,07    0,20    0,28    0,34
<b>Permanent antistatic</b>	PrEN 1815 < 2KV
<b>Surface resistance</b>	ISO/DIS 10965 –
<b>Tile size</b>	50 x 50 cm 60 x 60 cm on request
<b>Packing</b>	5m <sup>2</sup> per box
<b>Colours</b>	24
<b>Dimensional stability</b>	EN 986 Max -0.2%
<b>Contract rating</b>	Heavy contract

Shades may vary from batch to batch and should be checked before installation. Bürofloor carpet tiles must be installed according to our instructions and in accordance with the relevant British Standards.

Regular vacuum cleaning is recommended, spills and stains must be removed as part of a comprehensive maintenance plan.

We reserve the right to alter technical specification without prior notice.