

Vitesse

PRODUCT SPECIFICATION

Construction	Tufted Loop Pile
Machine	1/10th Gauge
Fibre	100% Solution Dyed Nylon
Primary Backing	100 grms/square metre
Secondary Backing (Latex)	750 grms/square metre
Bitumen plus non-woven fleece	3,000 grms/square metre
Pile Weight	500 grms/square metre
Total Weight	4,3000 grms/square metre
Pile Height	3.5 mm
Stitch Rate	43.50 stitches per 10cm
Stitch Density	171260 tufts/square metre
Tile Size	50cm x 50cm
Tiles per Box	20 or 5 square metres

PERFORMANCE

Flammability	BS 4790 Hot Metal Nut Test Low radius of char
Stroll Test	BS ISO 6356 Less than 2 KV
Dimensional Stability	Passes Aachen DIN 54318
Castor Wheel Test	Pass r = 2.8 BS EN 985
Static Loading	Not tested
Colour Fastness (Scale bad 1 to good 8)	BS EN ISO 105 6
Fastness to Water	BS EN ISO 105 5
Fastness to Shampoo	BS 1006 4-5
Fastness to Rubbing (Wet)	BS EN ISO 105 4-5
Fastness to Rubbing (Dry)	BS EN ISO 105 4-5